CATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

	icant's or agent's file 306 SCF	reference	FOR FURTHER A	CTION	See Form PCT/PEA/41	8
International application No. PCT/IB2004/003196			International filing data 30.09.2004	(day/month/year)	Priority date (day/mor	nth/year)
F42	D1.08	sification (IPO) or n	ational classification and li	ic		
	Icam ERNATIONAL T	ECHNOLOGIE	S, LLC et Al.			
1.	This report is the Authority under	International pre Article 35 and trai	eliminary examination rensmitted to the applican	port, established by t t according to Article	his International Prelimi 38.	nary Examining
2.						
3.	This report is also accompanied by ANNEXES, comprising:					
a. 🗵 sent to the applicant and to the International Bureau) a total of 5 sheets, as follows:						
	sheets of the description, claims and/or drawings which have been amended and are the basis of this reand/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).					asis of this report ption 607 of the
	beyon	ts which superse nd the disclosure lamental Box.	de earlier sheets, but w in the international app	hich this Authority cor lication as filed, as in	nsiders contain an amer dicated in Item 4 of Box	dment that goes No. I and the
	sequence	listing and/or tal	Bureau only) a total of (li ples related thereto, in c Listing (see Section 80	omputer readable for	ber of electronic carrier(m only, as Indicated in the Instructions).	s)) , containing a he Supplemental
4.	This report contains indications relating to the following items:					
1	Box No. 1	Basis of the opi	nion			
	☐ Box No. II	Priority				
	☐ Box No. III	Non-establishm	ent of opinion with rega	rd to novelty, inventiv	e step and industrial ap	plicability
	Box No. IV	Lack of unity of	invention			
	⊠ Bộx No. V	applicability; cit	ations and explanations) with regard to nove supporting such stat	ity, inventive step or ind ement	ustrial
	Box No. VI	Certain docume				
	☐ Box No. VII		in the International app			
	☐ Box No. VIII	Certain observa	ations on the Internation	al application		
Date	Date of submission of the demand			Date of completion of	this report	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
02.0	08.2005			15.12.2005		
Name and mailing address of the International				Authorized Officer		pad Pilina
preliminary examining authority: European Patent Office - P.B. 5818 Patentiaan 2 NL-2280 HV Rijswijk - Pays Bas Tel. +31 70 340 - 2040 Tx: 31 651 epo ni Fax: +31 70 340 - 3016				Lostetter, Y Telephone No. +31 70	9 540-1098	
l .						

(10/574377

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

IAP20 Rec d PCT/PTO 0 3 APR 2006 International application No. PCT/IB2004/003196

	Box No. 1 Basis of the rep	rort			
1.	With regard to the language, this report is based on the International application in the language in which it wa iled, unless otherwise indicated under this Item.				
	which is the language of international search publication of the international search.	translations from the original language into the following language , i a translation furnished for the purposes of: (under Rules 12.3 and 23.1(b)) ernational application (under Rule 12.4) ary examination (under Rules 55.2 and/or 55.3)			
2.	With regard to the elements* of the international application, this report is based on (replacement sheets have been furnished to the receiving Office In response to an invitation under Article 14 are referred to in report as "originally filed" and are not annexed to this report):				
	Description, Pages				
	1-9	as originally filed			
	Claims, Numbers				
	1-22	filed with telefax on 05.09.2005			
	Drawings, Sheets				
	12, 22	as originally filed			
	□ a sequence listing and/	or any related table(s) - see Supplemental Box Relating to Sequence Listing			
3.	 □ The amendments have resulted in the cancellation of: □ the description, pages □ the claims, Nos. □ the drawings, sheets/figs □ the sequence listing (specify): □ any table(s) related to sequence listing (specify): 				
4.	This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)). the description, pages the claims, Nos. the drawings, sheets/figs the sequence listing (specify): any table(s) related to sequence listing (specify):				
	* If item 4 applies,	some or all of these sheets may be marked "superseded."			

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/IB2004/003196

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)

Yes: Claims

1-22

No: Claims

Inventive step (IS)

Yes: Claims

Claims

1-22

Industrial applicability (IA)

Yes: Claims

No:

1-22

No: Claims

2. Citations and explanations (Rule 70.7):

see separate sheet

10/574377

International application No.

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (SEPARATE SHEET)

PCT/IB2004/003196

Re Item V

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following documents:

D1: DE-B-1278908 D2: WO-A-02/42711

2. The document D1 is regarded as being the closest prior art to the subject-matter of claim 1, and discloses (column 2, lines 19-30; column 3, lines 1-24; figure 1; the references in parentheses applying to this document):

A method of charging and blasting a drill hole (1) extending between a mouth thereof at a surface, and a blind end or bottom thereof remote from the mouth,

- the method steps of charging the drill hole including:
 - providing in the drill hole (1) at a relatively low level toward said bottom a lower layer (2) of a blasting substance, and a lower layer of a plunger material (3) proximately above the lower layer (2) of blasting substance;
 - providing in the drill hole (1) at a relatively high level remote from said bottom a higher layer of a blasting substance (2'), spaced a predetermined distance above said lower layer of plunger material (3) to form a spacing (6'), and proximately above said higher layer of a blasting substance (2'), a higher layer of plunger material (3');
 - placing Initiators (4) in association with the respective layers of blasting substances (2, 2') and connecting the initiators (4) to a controller (7) for actuating the initiators (4) at predetermined time intervals;
- the method steps of blasting the charged drill hole (1) including actuating the initiators (4) by means of the controller (7).

The subject-matter of claim 1 therefore differs from this known method in that:

- the higher layer of plunger material is located below the higher layer of a blasting substance;
- the method steps of blasting the charged drill hole further including propelling the

Form PCT/Separate Sheet/409 (Sheet 1) (EPO-January 2004)

PCT/IB2004/003196

lower layer of plunger material by means of the lower layer of blasting substance into the spacing, and propelling the higher layer of plunger material by means of the higher layer of blasting substance into said spacing; thereby causing the lower layer of plunger material and the higher layer of plunger material to impinge upon each other, and causing conversion of kinetic energy associated with the propelled layers of plunger material into pressure or shock waves to effect destruction of rock in the surrounding material.

The subject-matter of claim 1 is therefore new (Article 33(2) PCT).

The problem to be solved by the present invention may be regarded as reducing the amount of explosives required to conduct blasting operations.

The solution to this problem proposed in claim 1 of the present application is considered as involving an inventive step (Article 33(3) PCT) for the following reason: Although the feature of providing a layer of plunger material below a layer of blasting substance, which layer of plunger material is forced downwards at a high velocity upon detonation of the blasting substance is described in document D2 (cf. page 9, line 25 - page 10, line 16), the skilled person would not regard it as a normal design option to locate the higher layer of plunger material below the higher layer of blasting substance in the drill hole arrangement described in document D1 in order to solve the problem posed because the feature of causing the lower layer of plunger material and the higher layer of plunger material to impinge upon each other is not disclosed nor suggested in document D2, nor in any of the documents cited in the international search report.

- 3. The same reasoning applies, mutatis mutandis, to the subject-matter of the corresponding Independent claims 12, 13 and 22, which therefore are also considered new and inventive.
- 4. Claims 2-11 and 14-21 are dependent on claims 1 and 13 and as such also meet the requirements of the PCT with respect to novelty and inventive step.

Form PCT/Separate Sheet/409 (Sheet 2) (EPO-January 2004)



15

20

25

30

P.43

697.0N





10/574377

10

IAPZO REC'OPCT/PTO 03 APR 2006

CLAIMS:

1. A method of charging and blasting a drill hole extending between a mouth thereof at a surface, and a blind end or bottom thereof remote from the mouth, the method steps of charging the drill hole including

providing in the drill hole at a relatively low level toward said bottom a lower layer of a blasting substance, and a lower layer of a plunger material proximately above the lower layer of blasting substance;

providing in the drill hole at a relatively high level remote from said bottom a higher layer of a plunger material, spaced a predetermined distance above said lower layer of plunger material to form a spacing, and proximately above said higher layer of plunger material, a higher layer of a blasting substance;

placing initiators in association with the respective layers of blasting substances and connecting the initiators to a controller for actuating the initiators at predetermined time interval.

the method steps of blasting the charged drill hole including

actuating the initiators by means of the controller, thereby propelling the lower layer of plunger material by means of the lower layer of blasting substance into said spacing, and propelling the higher layer of plunger material by means of the higher layer of blasting substance into said spacing; thereby causing the lower layer of plunger material and the higher layer of plunger material to impinge upon each other, and causing conversion of kinetic energy associated with the propelled layers of plunger material into pressure or shock waves to effect destruction of rock in the surrounding material.

2. A method as claimed in Claim 1, in which the spacing between opposing surfaces of respectively said lower layer of plunger material and said higher layer of plunger material is between about 0,5 m and about 3 m.

C-Ward F1810F High Fower Shot Claims Amended Sept Dá SCF/ove 05 Sep 2005 2:10 PM









11

- 3. A method as claimed in Claim 1 or Claim 2 in which the respective layers of plunger material are flowable material allowing placement in the drill hole at the respective desired positions.
- 5 4. A method as claimed in any one of Claim 1 to Claim 3 inclusive, including tamping the drill hole proximate its mouth.
 - 5. A method as claimed in any one of Claim 1 to Claim 4 inclusive in which said relatively low level is spatially adjacent a bottom of the drill hole and spaced above the bottom by a predetermined distance.
 - 6. A method as claimed in Claim 5 in which the spacing between said relatively low level and the bottom is between about 0,5 m and about 3 m.
- 7. A method as claimed in Claim 5 or Claim 6, including supporting in each respective case the layer of plunger material and the layer of blasting substance on a plug capable of being positioned in the drill hole at a predetermined level.
- 20 8. A method as claimed in any one of Claim 5 to Claim 7 inclusive, including providing plunger material below the lower layer of blasting substance to provide a lower composite layer, providing plunger material above the higher layer of blasting substance to provide a higher composite layer, and providing one or more further composite layers of blasting substance and plunger material in the drill hole, with spacings in-between, in series along the drill hole.
 - 9. A method as claimed in any one of Claim 1 to Claim 4 inclusive, in which the lower layer of blasting substance is positioned proximate and is supported on the bottom of the drill hole.

30

C: Word F18306 Righ Power Shot Claims Amended Sept G5 SCF/cve C5 Sep 2005 2:10 PM







15

20

25



12

- 10. A method as claimed in any one of Claim 1 to Claim 9 inclusive which includes actuating the initiators at time intervals to initiate the respective blasting substances simultaneously.
- 5 11. A method as claimed in Claim 10 which includes actuating the initiators in a way selected from electrically, electronically, or pyrotechnically.
 - 12. A method of mining including carrying out the method of any one of Claim 11 on each of an array of drill holes.

13. A charged drill hole extending between a mouth thereof at a surface, and a blind end or bottom thereof remote from the mouth, including within the drill hole.

a lower layer of a blasting substance at a relatively low level toward said bottom, and a lower layer of a plunger material proximately above the lower layer of blasting substance;

a higher layer of a plunger material at a relatively high level remote from said bottom, and spaced a predetermined distance above said lower layer of plunger material such as to form a spacing therebetween, and proximately above said higher layer of plunger material, a higher layer of a blasting substance:

initiators placed in association with the respective layers of blasting substances and having connectors for connection to a controller for actuating the initiators at predetermined time intervals,

an arrangement being provided wherein the lower and higher layers of plunger material oppose each other spatially, each layer of plunger material being backed by a layer of blasting substance, such that, in use, on actuation of the layers of blasting substance the layers of plunger material are propelled toward each other, to impinge upon each other and to convert kinetic energy

30

C: Nord P18306 Klein Power Shot Claims Amended Sept 05 SCF/cve 05 Sep 2005 2:10 9M





associated with the propelled layers of plunger material into pressure or shock waves to destruct surrounding material.

- 14. A charged drill hole as claimed in Claim 13 in which the spacing between opposing surfaces of respectively said lower layer and said higher layer of plunger material is between about 0,5 m and about 3 m.
- 15. A charged drill hole as claimed in Claim 13 or Claim 14 in which the respective layers of plunger material are flowable material allowing placement in the drill hole at the respective desired positions.
 - 16. A charged drill hole as claimed in any one of Claim 13 to Claim 15. Inclusive, including tamping material closing the drill hole proximate its mouth.
- 15 17. A charged drill hole as claimed in any one of Claim 13 to Claim 16 inclusive in which said relatively low level is spatially adjacent a bottom of the drill hole and spaced above the bottom by a predetermined distance.
- 18. A charged drill hole as claimed in Claim 17 in which the spacing is between about 0,5 m and about 3 m.
 - 19. A charged drill hole as claimed in Claim 17 or Claim 18 in which, in each respective case, the layer of plunger material and the layer of blasting substance is supported on a plug positioned in the drill hole at a predatermined level.
 - 20. A charged drill hole as claimed in any one of Claim 17 to Claim 19 inclusive, including plunger material provided below the lower layer of blasting substance to form a lower composite layer, plunger material provided above the higher layer of blasting substance to form a higher composite layer, and one or

Diward Figure Righ Power Shot Claims Amended Sept 05 SCT/cve 05 Sep 2005 2:10 FK





25

30

more further composite layers of blasting substance and plunger material, with spacings in-between, in series along the drill hole.

- 5 21. A charged drill hole as claimed in any one of Claim 13 to Claim 16 inclusive, in which the lower layer of blasting substance is proximate the bottom and is supported on the bottom.
- 22. A blasting operation including an array of blast holes each in accordance with any one of Claim 13 to Claim 21 inclusive.

C: Word F19306 Kigh Power Shot Claims Amended_80pt_05 SCF/eve 05 Sep 3005 2:10 PM



